

DATA SHEET

Safety tester **KT 1885L**



Safety tester KT 1885L
Plug-in 19" / 5 HU

Description	Fully automatic safety tester with 500 VA / 100 mA high voltage test. Potential-free, fully-electronic generators, extended voltage range supply 90 V up to 250 V, 50/60 Hz.	
High voltage test AC	Voltage range	100 up to 5,500 V
	Current range	0 up to 100 mA
	Short circuit current	> 200 mA
High voltage test DC	Voltage range	100 up to 6,000 V
	Current range	0 up to 100 mA
	Residual ripple	< 3 %
Insulation measurement DC	Voltage range	100 up to 6,000 V
	Measuring range (voltage dependent)	250 k Ω up to 10 G Ω
ARC detection	Range	0 up to 100%
Ground bond test	Measuring range	0 up to 10 Ω
	Test current AC	1 up to 30 A
Equivalent leakage current test	Measuring range	0 up to 10 mA
	Test current AC	50 up to 270 V
Continuity test	Measuring range	0 up to 600 mA
Resistance measurement	Measuring range	0 up to 1,000 Ω
Subjective tests	Picture step / text step	subjective or informative
General data	Dimensions (HxWxD) and weight	222 x 483 x 491 mm / approx. 25.0 kg 8.7 x 19.0 x 19.3 in. / approx. 55.1 lbs.
	Mains supply	90 up to 250 V, 50 Hz / 60 Hz
Interfaces	Computer interfaces	2 x USB, RS 232, Ethernet / LAN, CAN
	Digital interface 24 VDC	8 input + 8 output
	Analogue interface 10 VDC	2 x input + 1 x output
Operation	Touch	10.1"-TFT-colour